Machining Instructions for M/E 8.8 Ford Housing Ends to fit 1993 Mustang Cobra or 1994-2004 Mustang with factory disc brakes (GT or Cobra)

Note: **To retain the ABS feature you must use Moser Axles and the Moser Exciter rings with the Moser 8.8 ends.**

1. The factory cast caliper mounts require machining to fit the factory disc brakes on your new housing ends.
2. Overlay your retainer plate on the wheel side of the caliper mount plate making sure the bolt holes are properly aligned.
3. Using the retainer plate as your template, make an outline of the retainer plate on your caliper mount plate.
4. Machine/Mill out the area inside the newly drawn line to a depth equal to that of the factory recessed holes. (See Figure A)
5. You should now be ready to install your axles and brakes on your new housing ends.

Figure A.



Moser Engineering Inc. disclaims warranty of any kind, including but not limited to an expressed or implied warranty of quality or fitness for any purpose. No warranty of any kind, expressed or implied, as to the quality or suitability of this product for any use, is hereby made by Moser Engineering. The buyer assumes all risk and liability resulting from the use of the goods. Seller neither assumes nor authorizes any person to assume for seller any other liability in connection with the sale or use of the goods sold, and there are no oral agreements or warranties collateral to or effecting the disclaimer or warranty. Included in said disclaimer is service of or remanufacturing performed by Moser Engineering on any product.

102 Performance Drive | Portland, IN 47371 | 260.726.6689 | 260.726.4159 Fax | info@moserengineering.com | www.moserengineering.com